

TECHNICAL DATA SHEET

HEAVY DUTY (HD) GLAZE

A water-based durable heavy duty interior glaze for high traffic areas to allow for easier general cleaning and as a sacrificial coating for the removal of graffiti when used over Colorfects Finishes.

AVAILABILITY

Colour Range	Clear
Packaging	5 litre.

PROPERTIES

Drying Time	Under normal drying conditions 2 hours. Allow for adequate ventilation during the drying period. Recoatable after 6 hours.
Finish	Gloss.
Composition	Pigment: None. Binder: Polyurethane dispersion. Solvent: Water.
Spreading Rate	20m ² per litre on smooth surfaces.
Wet Film Thickness	50 micrometres at 20m ² per litre.
Dry Film Thickness	10 micrometres at 20m ² per litre.
Volume Solids	21%.
Flash Point	Not applicable.
VOC Content	EU limit value for this product (cat.A/e): 150 g/l (2007) / 130 g/l (2010) This product contains max. 37 g/l VOC.
Limitations	For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New Surfaces	None required. Apply as soon as possible after Colorfects Finish has dried and before surfaces are contaminated.
--------------	--

APPLICATION

Stir before use. Apply two coats systematically using a good quality 4" (100mm) synthetic brush, a short pile roller, or a good quality medium pile roller. Ensure all areas are fully and evenly coated. Maintain a wet edge.

CLEANING

Return surplus material to container. Wash with clean water immediately after use.

MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt. For the removal of graffiti use a proprietary graffiti system in accordance with the manufacturer's instructions.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000 : Part 12 : 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information.

For help or more information contact the Crown Trade Customer Relations Team on:

Tel: 0845 389 9583

Fax: 0845 389 9584

e-mail: info@crowntrade.co.uk

website: www.crowntrade.co.uk

This information is correct at date of issue July 2008.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Email: info@crowntrade.co.uk

Website: www.crowntrade.co.uk