

STERACRYL MOULD INHIBITING DURABLE ACRYLIC EGGSHELL

A water-based, durable, mould inhibiting acrylic eggshell for use on interior walls and woodwork. Steracryl Mould Inhibiting Acrylic Eggshell contains fungicide to maintain decorated surfaces by inhibiting the development of mould growths on the paint film.

AVAILABILITY

Colour Range	White and Pastel Base, refer to current Crown Trade Literature.
Packaging	5 litre.

PROPERTIES

Drying Time	Under normal drying conditions touch dry in 2 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.
Finish	Mid sheen.
Composition	Pigment: Titanium Dioxide, coloured pigments and extenders. Binder: Acrylic Polymer. Solvent: Water.
Spreading Rate	Up to 14m ² per litre on smooth surfaces.
Wet Film Thickness	71 micrometres at 14m ² per litre.
Dry Film Thickness	25 micrometres at 14m ² per litre.
Volume Solids	35.6% White, other colours will vary.
Flash Point	Not applicable
VOC Content	EU limit value for this product (cat.A/b): 100 g/l (2010). This product contains max. 99 g/l VOC.
Limitations	For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New Surfaces	<p>All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the material to be applied. Powdery, polished plaster or dense surfaces should be primed with Crown Trade Alkali Resisting Sealer or Crown Trade P.S.B Stain Block Primer . Porous surfaces should be 'mist' coated with Crown Trade Steracryl Mould Inhibiting Durable Acrylic Eggshell thinned with up to 40% clean water.</p> <p>Timber</p> <p>All surfaces must be suitably dry, and free from anything that will interfere with the adhesion of the materials to be applied. Rub down with a suitable grade of abrasive paper. Remove all dust. Treat knots with two thin coats of fresh knotting. Fill any fixing holes, open joints and shallow surface defects with Sandtex Trade Ready Mixed Filler or 2 pack proprietary filler. Rub down with a suitable grade of abrasive paper. Remove all dust. Primer with one coat of Crown Trade Water Based Primer Undercoat. Prior to priming the moisture content of the substrate should not exceed 18%. Prime with one coat of Crown Trade Wood Primer.</p>
Previously Decorated Surfaces	<p>All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects with Sandtex Trade Ready Mixed Filler. Patch prime bare and filled areas with Crown Trade Alkali Resisting Sealer or Crown Trade P.S.B Stain Block Primer. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any</p>

glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. Any areas likely to cause staining and/or bleeding must be patch primed with one coat of Crown Trade Alkali Resisting Sealer or Crown Trade P.S.B Stain Block Primer. Bring forward patch primed areas with one coat of Crown Trade Steracryl Mould Inhibiting Durable Acrylic Eggshell.

Timber

All surfaces must be dry, and free from anything that will interfere with the adhesion of the materials to be applied. Remove all loose, failing or suspect paint. Remove Grey and denatured surfaces by rubbing down with abrasive paper. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Treat with two thin coats of fresh knotting. Fill any fixing holes, open joints and shallow surface defects with Sandtex Trade Ready Mixed Filler or 2 pack proprietary filler. Rub down with a suitable grade of abrasive paper. Remove all dust. Spot prime bare and filled areas with one coat of Crown Trade Water Based Primer Undercoat.

COATING SYSTEM

Apply two coats as required. Certain colours may require additional coats to give complete obliteration.

APPLICATION

Stir well before use. Apply using a good quality paint brush or medium pile roller. For spray application, dilution up to 15% may be required, depending on type and make of spray equipment. For further information please contact the Crown Paints Customer Relations Team. Always intermix packs for colour consistency. Please check for colour accuracy prior to application. Crown Paints is not liable for decorating costs caused as a result of an incorrect colour being applied.

CLEANING

Return surplus material to container. Clean with clean water immediately after use. For further information contact the Crown Paints Customer Relations Team.

MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration, surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information. For help or more information contact the Crown Trade Customer Relations Team on:

Tel: 0845 389 9583

Fax: 0845 389 9584

e-mail: info@crowntrade.co.uk

website: www.crowntrade.co.uk

This information is correct at date of issue October 2011



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Tel: 01254 704951 Fax: 01254 870155

Email: info@crowntrade.co.uk

Website: www.crowntrade.co.uk