

STERACRYL MOULD INHIBITING MATT FINISH

A water-based high opacity matt mould inhibiting finish suitable for use on interior wall and ceiling surfaces. Steracryl contains fungicide to maintain decorated surfaces in good condition when used in humid environments.

AVAILABILITY

Colour Range 20 BS colours & White, refer to current Crown Trade Literature.

Packaging 5 litre.

PROPERTIES

Drying Time Under normal drying conditions recoatable after 4 hours. Allow for adequate ventilation during the drying period.

Finish Matt.

Composition Pigment: Titanium Dioxide, coloured pigments and extenders.
Binder: Styrene acrylic
Solvent: Water.

Spreading Rate Up to 14m² per litre on smooth surfaces.

Wet Film Thickness 71 micrometres at 14m² per litre.

Dry Film Thickness 25 micrometres at 14m² per litre.

Volume Solids 35% Brilliant White other colours will vary.

Flash Point Not applicable.

VOC Content EU limit value for this product (cat.A/i): 140 g/l (2007) / 140 g/l (2010) This product contains max. 2 g/l VOC.

Limitations For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New Surfaces All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the material to be applied. Powdery, polished plaster or dense surfaces should be primed with Crown Trade Alkali Resisting Sealer. Porous surfaces should be 'mist' coated with Crown Trade Steracryl thinned with up to 20% clean water.

Previously Decorated Surfaces All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects with Sandtex Trade Ready Mixed Filler. Patch prime bare and filled areas with Crown Trade Alkali Resisting Sealer. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. Any areas likely to cause staining and/or bleeding must be patch primed with one coat of Crown Trade Alkali Resisting Sealer. Bring forward patch primed areas with one coat of Crown Trade Steracryl.

COATING SYSTEM

Apply two coats as required.

APPLICATION

Stir well before use. Apply by brush or roller. For airless spray (dilution may be required) please contact the Crown Paints Customer Relations Team.

MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

CLEANING

Return surplus material to container. Clean with a proprietary cleaner immediately after use. For further information contact the Crown Paints Customer Relations Team.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000 : Part 12 : 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information.

For help or more information contact the Crown Trade Customer Relations Team on:

Tel: 0845 389 9583

Fax: 0845 389 9584

e-mail: info@crowntrade.co.uk

website: www.crowntrade.co.uk

This information is correct at date of issue July 2008.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Email: info@crowntrade.co.uk

Website: www.crowntrade.co.uk