

GRAFFITI REMOVER

Crown Trade Timonox Graffiti Remover is specially formulated for use on surfaces previously coated with Crown Trade Timonox Anti Graffiti Flame Retardant Glaze. Allows repeated removal of unsightly graffiti without compromising the system. Removes the following: all paints (including aerosol spray paints), graffiti shadow, marker pens & crayons.

AVAILABILITY

Colour not applicable.

Packaging 500 ml (trigger spray bottle).

PROPERTIES

Drying time If redecorating, after graffiti removal, wash treated areas with clean water and allow to dry.

Finish not applicable.

Composition Active agent: Special blend of surfactants.
Binder: None
Solvent: Water.

Spreading rate Up to 3m² per 500 ml depending on type of graffiti coating and number of treatments / applications.

Wet film thickness not applicable.

Dry film thickness not applicable

Volume solids not applicable

Flash point not applicable.

VOC content not applicable.

GRAFFITI REMOVAL Shake the container well before use.

If using Crown Trade Timonox Graffiti Remover on surfaces other than the Timonox Anti Graffiti Flame Retardant Glaze, always check surface compatibility by applying a small amount to an inconspicuous area before attempting removal. The Graffiti Remover should be left on the surface for the minimum period necessary to remove the graffiti (longer times may result in softening of the substrate / underlying coating).

Spray the Graffiti Remover onto the affected area from a distance of approximately 6 – 12 inches (15 – 30 cm). Leave for 1 – 2 minutes and remove with a damp cloth.

If further treatment is required for stubborn stains, spray the Graffiti Remover onto the cloth and wipe away remaining residues.

If nozzle clogs during use, wash out with clean, warm soapy water.

Protective gloves and glasses are recommended during graffiti removal and cleaning.

CLEANING Clean equipment with water immediately after use.

MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt. Remove any graffiti as described above.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact our Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Final results cannot be guaranteed by the manufacturer as it has no control over the conditions under which its products are applied.

For help or more information contact our Customer Relations Team on 0845 389 9583. Before using this product please ensure you have the latest information. The information is correct at date of issue April 2010.



Crown Paints Ltd

Crown House, Hollins Road, Darwen, Lancs BB3 0BG
Tel: 0845 389 9583 Fax: 0845 389 9584 Email: info@crowntrade.co.uk
Website: www.crowntrade.co.uk