

## WASHABLE FLAT MATT

A water-based premium quality washable flat matt emulsion for interior use. Specially to provide a modern coating with the unique benefit of good washability whilst retaining the characteristics of a traditional flat matt finish.

### AVAILABILITY

Colour Range White.

Packaging 5 litre.

### PROPERTIES

Drying Time Under normal drying conditions touch dry 1-2 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.

Finish Matt.

Composition Pigment: Titanium Dioxide, coloured pigments and extenders.  
Binder: Styrene acrylic polymer.  
Solvent: Water.

Spreading Rate Up to 12m<sup>2</sup> per litre on smooth surfaces.

Wet Film Thickness 83 micrometres at 12m<sup>2</sup> per litre.

Dry Film Thickness 32 micrometres at 12m<sup>2</sup> per litre.

Volume Solids 39%

Flash Point Not applicable.

VOC Content EU limit value for this product (cat.A/a): 75 g/l (2007) / 30 g/l (2010) This product contains max. 2 g/l VOC.

Limitations For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

### PREPARATION

New Surfaces All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed with Crown Trade Alkali Resisting Sealer. Porous surfaces should be 'mist' coated with Crown Trade Acrylic Primer thinned with 10% clean water.

Previously decorated surfaces All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects with Sandtex Trade Ready Mixed Filler. Patch prime bare and filled areas with Crown Trade Acrylic Primer thinned 10% with clean water. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas still contaminated with substances likely to cause staining and/or bleeding, patch prime with one coat of Crown Trade Alkali Resisting Sealer. Bring forward patch primed areas with one coat of Crown Trade Washable Flat Matt.

## COATING SYSTEM

Apply two coats as required.

## APPLICATION

Stir well before use. Apply by brush, roller or spray. For airless spray (dilution may be required). For further information contact the Crown Trade Customer Relations Team.

**Note:** When thinning is required for application by spray the minimum dry film thickness for two coats must not be less than 66 micrometres to retain subsequent washability.

## CLEANING

Return surplus material to container. Wash with clean water immediately after use.

## MAINTENANCE INFORMATION FOR CDM FILE HEALTH AND SAFETY

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

## GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000 : Part 12 : 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information. For help or more information contact the Crown Trade Customer Relations Team on:  
Tel: 0845 389 9583  
Fax: 0845 389 9584  
e-mail: [info@crowntrade.co.uk](mailto:info@crowntrade.co.uk)  
website: [www.crowntrade.co.uk](http://www.crowntrade.co.uk)

This information is correct at date of issue January 2009.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Email: [info@crowntrade.co.uk](mailto:info@crowntrade.co.uk)

Website: [www.crowntrade.co.uk](http://www.crowntrade.co.uk)